

View Online at <https://aerobasegroup.com/nsn/5962-01-350-4142>

Overall Length:

1.060 inches

Overall Height:

0.400 inches

Body Length:

1.060 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.130 inches and 0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

High speed and 3-state output and monolithic and burn in and w/enable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

13 input

Design Function And Quantity:

1 multiplexer and 1 register

Case Outline Source And Designator:

D-8 mil-m-38510

Current Rating Per Characteristic:

70.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

10.00 input picofarads and 20.00 output picofarads

Time Rating Per Characteristic:

94.00 nanoseconds propagation delay time, high to low level output and 94.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0