

View Online at <https://aerobasegroup.com/nsn/5962-01-350-4143>

Maximum Power Dissipation Rating:

450.0 milliwatts

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Storage Temperature Range:

-65.0 to 150.0 degrees celsius

Features Provided:

Thin film and electrostatic sensitive and monolithic and parallel operation

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

15 input

Design Function And Quantity:

2 converter, digital to analog

Current Rating Per Characteristic:

2.00 milliamperes supply

Terminal Surface Treatment:

Solder

Product Name:

Buffered multiplying d/a converter

Voltage Rating And Type Per Characteristic:

17.0 volts power source

Capitance Rating Per Characteristic:

15.00 input picofarads

Time Rating Per Characteristic:

300.00 nanoseconds propagation delay

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0