

View Online at <https://aerobasegroup.com/nsn/5962-01-350-4143>

**Maximum Power Dissipation Rating:**

450.0 milliwatts

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Storage Temperature Range:**

-65.0 to 150.0 degrees celsius

**Features Provided:**

Thin film and electrostatic sensitive and monolithic and parallel operation

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

15 input

**Design Function And Quantity:**

2 converter, digital to analog

**Current Rating Per Characteristic:**

2.00 milliamperes supply

**Terminal Surface Treatment:**

Solder

**Product Name:**

Buffered multiplying d/a converter

**Voltage Rating And Type Per Characteristic:**

17.0 volts power source

**Capitance Rating Per Characteristic:**

15.00 input picofarads

**Time Rating Per Characteristic:**

300.00 nanoseconds propagation delay

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0