NSN 5962-01-351-1782

Memory Microcircuit - Page 1 of 2



	arvu
View Online at https://aerobasegroup.com/nsn/5962-01-351-1782	
Overall Length:	
1.060 inches	
Overall Height:	
0.400 inches	
Body Length:	
1.060 inches	
Body Width:	
Between 0.220 inches and 0.310 inches	
Body Height:	
Between 0.130 inches and 0.185 inches	
Maximum Power Dissipation Rating:	
1.1 watts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
W/clock and programmed and high impedance and monolithic and bidirectional	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
16 input	
Case Outline Source And Designator:	
D-8 mil-m-38510	
Current Rating Per Characteristic:	
90.00 milliamperes reverse current, dc absolute	
Terminal Surface Treatment:	
Solder	
Product Name:	
And-or invert gate array	
Voltage Rating And Type Per Characteristic:	
-0.5 volts power source and 12.0 volts power source	
Time Rating Per Chacteristic:	
50.00 nanoseconds propagation delay time, high to low level output and 50.00 nanoseconds propagation delay time, low to high output	n level
Memory Device Type:	
Pal	
Test Data Document:	
06006 mil atd 882 atandard (includes industry or association standards, individual manufastures, standards, sta	

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-351-1782

Memory Microcircuit - Page 2 of 2

AeroBase Group

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0