## NSN 5962-01-351-4926

Linear Microcircuit - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5962-01-351-4926

Overall Length:
0.405 inches
Overall Height:
0.400 inches
Body Length:
0.405 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
250.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
High speed and monolithic and w/field effect transistor switch
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 amplifier, operational, general purpose
Case Outline Source And Designator:
D-4 mil-m-38510
Current Rating Per Characteristic:
2.20 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-20.0 volts power source and 20.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:

## NSN 5962-01-351-4926

Linear Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

