# NSN 5962-01-351-4928

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-351-4928

# **Body Length:**

Between 0.342 inches and 0.358 inches

# **Body Width:**

Between 0.342 inches and 0.358 inches

# **Body Height:**

Between 0.060 inches and 0.100 inches

# **Maximum Power Dissipation Rating:**

400.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

# **Features Provided:**

Monolithic

#### **Inclosure Material:**

# Ceramic

**Inclosure Configuration:** 

Leadless flat pack

# **Input Circuit Pattern:**

2 input

# **Design Function And Quantity:**

1 amplifier, operational, general purpose

# **Case Outline Source And Designator:**

C-2 mil-m-38510

# **Current Rating Per Characteristic:**

5.00 milliamperes reverse current, dc absolute

# **Terminal Surface Treatment:**

Solder

# **Product Name:**

Operational amplifier, low offset

# Voltage Rating And Type Per Characteristic:

-22.0 volts power source and 22.0 volts power source

# **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# **Terminal Type And Quantity:**

20 leadless

# Shelf Life:

N/a

# Unit Of Measure:

# **Demilitarization:**

No

# NSN 5962-01-351-4928

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

