

View Online at <https://aerobasegroup.com/nsn/5962-01-351-4942>

Body Length:

0.540 inches

Body Width:

Between 0.245 inches and 0.300 inches

Body Height:

Between 0.045 inches and 0.090 inches

Maximum Power Dissipation Rating:

148.5 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

5895-01-299-3419 converter, signal

Features Provided:

W/enable and monolithic and w/clock and w/disable and low power and schottky and 3-state output

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

8 flip-flop, d-type

Case Outline Source And Designator:

F-9 mil-m-38510

Current Rating Per Characteristic:

27.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

With transparent latch

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

23.00 nanoseconds propagation delay time, high to low level output and 26.00 nanoseconds propagation delay time, low to high level output

Special Features:

Nuclear hardness critical items

Nuclear Hardness Critical Feature:

Hardened

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0