## NSN 5962-01-351-4980

Memory Microcircuit - Page 1 of 2

Between 0.510 inches and 0.620 inches

Body Length: 2.435 inches Body Width:



View Online at https://aerobasegroup.com/nsn/5962-01-351-4980

1. O -5 S	.210 inches  laximum Power Dissipation Rating: .0 watts  Operating Tempurature Range: 55.0/+125.0 degrees celsius
1. O -5 S	.0 watts  Operating Tempurature Range:
o -5 s	Operating Tempurature Range:
{5 <b>S</b> {6	
<b>S</b>	55.0/+125.0 degrees celsius
-6	
	storage Tempurature Range:
_	65.0/+150.0 degrees celsius
F	eatures Provided:
В	surn in and monolithic and static operation
Ir	nclosure Material:
С	Ceramic Ceramic
Ir	nclosure Configuration:
D	Dual-in-line
O	Output Logic Form:
С	Complementary-metal oxide-semiconductor logic
Ir	nput Circuit Pattern:
4	4 input
С	case Outline Source And Designator:
D	0-14 mil-m-38510
С	current Rating Per Characteristic:
6	00.00 milliamperes reverse current, dc absolute
Т	erminal Surface Treatment:
G	Gold
Р	Product Name:
M	ficrocircuit, digital, memory static ram
٧	oltage Rating And Type Per Characteristic:
-(	0.5 volts power source and 7.0 volts power source
Т	ime Rating Per Chacteristic:
4	5.00 nanoseconds access
M	lemory Device Type:
R	tam
Р	recious Material And Location:
Т	erminal surfaces gold
Р	recious Material:
G	Gold
Т	est Data Document:
9	6906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)

## NSN 5962-01-351-4980

Memory Microcircuit - Page 2 of 2



ī	ermina	ı	Type	Δnd	Qua	antity.
ı	CHILLING	41	INDE	Allu	wu	aiititv.

48 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0