## NSN 5962-01-351-5709



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-351-5709 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 77.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 5895-01-299-3419 **Features Provided:** Burn in and bipolar and low power and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 4 multiplexer, one to eight line

**Case Outline Source And Designator:** 

F-5 mil-m-38510

**Terminal Surface Treatment:** 

Solder

**Product Name:** 

Microcircuit, digital, quad 1-of-8 data selector/multiplexer

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

**Test Data Document:** 

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

16 flat leads

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5962-01-351-5709

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0