NSN 5962-01-351-5710

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-351-5710

| Body Length: |
|--|
| 0.440 inches |
| Body Width: |
| Between 0.245 inches and 0.285 inches |
| Body Height: |
| Between 0.045 inches and 0.085 inches |
| Maximum Power Dissipation Rating: |
| 104.5 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 5895-01-299-3419 |
| Features Provided: |
| Burn in and low power and schottky |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 8 input |
| Design Function And Quantity: |
| 6 flip-flop, d-type |
| Case Outline Source And Designator: |
| F-5 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Microcircuit, digital, d-type flip-flop |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 7.0 volts power source |
| Special Features: |
| Nuclear hardness critical items |
| Nuclear Hardness Critical Feature: |
| Hardened |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |

16 flat leads

NSN 5962-01-351-5710

Digital Microcircuit - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0