

View Online at <https://aerobasegroup.com/nsn/5962-01-351-5723>

**Overall Height:**

0.400 inches

**Body Length:**

1.280 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

1.2 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Radar set an/sps-4 (v) 7

**Features Provided:**

Hermetically sealed and burn in and monolithic and electrostatic sensitive and ultraviolet erasable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

22 input

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Current Rating Per Characteristic:**

100.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Product Name:**

And-or-logic array

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:**

10.00 input picofarads and 10.00 output picofarads

**Time Rating Per Characteristic:**

25.00 nanoseconds delay

**Memory Device Type:**

Pal

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0