NSN 5962-01-351-6197

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-351-6197 **Body Length:** 0.440 inches **Body Width:** 0.285 inches **Body Height:** 0.085 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 5895-01-299-3419 converter, signal data **Features Provided:** Monolithic and high speed and high reliability **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** Quad 1 input **Design Function And Quantity:** 4 driver, line differential **Case Outline Source And Designator:** F-5 mil-m-38510 **Current Rating Per Characteristic:** 90.00 milliamperes forward current, nonrepetitive, peak total value absolute **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts input **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5962-01-351-6197

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0