NSN 5962-01-351-6199

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-351-6199
Overall Length:
1.060 inches
Overall Height:
0.400 inches
Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Satellite communications terminal an/usc-3 (v) 1
Features Provided:
Hermetically sealed and monolithic and 3-state output and w/clock and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
10 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 flip-flop, d-type
Case Outline Source And Designator:
D-8 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
40.00 nanoseconds propagation delay time, high to low level output and 36.00 nanoseconds propagation delay time, low to high level
output
Special Features

Test Data Document:

Nuclear hardness critical item

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-351-6199

Digital Microcircuit - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0