

View Online at <https://aerobasegroup.com/nsn/5962-01-351-6203>

**Overall Length:**

0.640 inches

**Overall Height:**

Between 0.045 inches and 0.090 inches

**Overall Width:**

Between 0.800 inches and 1.160 inches

**Body Length:**

0.640 inches

**Body Width:**

Between 0.300 inches and 0.420 inches

**Body Height:**

Between 0.045 inches and 0.090 inches

**Maximum Power Dissipation Rating:**

484.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

5895-01-299-3419 converter, signal

**Features Provided:**

3-state output and bipolar and low power and schottky and monolithic and w/clock and w/enable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

22 input

**Design Function And Quantity:**

8 register and 8 transceiver

**Case Outline Source And Designator:**

F-6 mil-m-38510

**Current Rating Per Characteristic:**

88.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

20.00 nanoseconds propagation delay time, high to low level output and 35.00 nanoseconds propagation delay time, low to high level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0