NSN 5962-01-351-6205

Digital Microcircuit - Page 1 of 2



standards, etc.).

View Online at https://aerobasegroup.com/nsn/5962-01-351-6205

Body Length:
0.390 inches
Body Width:
0.260 inches
Body Height:
0.085 inches
Maximum Power Dissipation Rating:
8.2 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
5895-01-299-3419 converter, signal data
Features Provided:
Monolithic and bipolar and low power
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 gate, nand
Case Outline Source And Designator:
F-2 mil-m-38510
Terminal Surface Treatment:
Solder
Product Name:
Positive nand gate
Voltage Rating And Type Per Characteristic:
7.0 volts input
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

NSN 5962-01-351-6205

Digital Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

