## NSN 5962-01-351-7246

Linear Microcircuit - Page 1 of 2

Overall Length: 0.785 inches Overall Height: 0.400 inches



View Online at https://aerobasegroup.com/nsn/5962-01-351-7246

Body Length:	
0.785 inches	
Body Width:	
Between 0.220 inches and 0.310 inches	
Body Height:	
Between 0.140 inches and 0.185 inches	
Maximum Power Dissipation Rating:	
400.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
End Application:	
Satellite communications terminal an/usc-3 (v) 1	
Features Provided:	
Monolithic	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Dual-in-line	
Input Circuit Pattern:	
2 channel	
Criticality Code Justification:	
Feat	
Design Function And Quantity:	
1 switch, analog, single pole double throw	
Case Outline Source And Designator:	
D-1 mil-m-38510	
Current Rating Per Characteristic:	
30.00 milliamperes reverse current, dc microamperes	
Terminal Surface Treatment:	
Solder	
Product Name:	
Analog switch with driver	
Voltage Rating And Type Per Characteristic:	
36.0 volts power source	
Capitance Rating Per Characteristic:	
14.00 input picofarads and 14.00 output picofarads	

## NSN 5962-01-351-7246

Linear Microcircuit - Page 2 of 2



Special	Features:
---------	-----------

Nuclear hardness critical item

**Test Data Document:** 

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

14 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

Fiig:

A458a0