NSN 5962-01-351-9028

Memory Microcircuit - Page 1 of 1



propagation delay time, low to high level

View Online at https://aerobasegroup.com/nsn/5962-01-351-9028

Body Lengtl	с.
1.060 inches	
Body Width:	
0.310 inches	
Body Height	:
0.185 inches	
Maximum Po	ower Dissipation Rating:
2.0 watts	
Operating To	empurature Range:
-55.0/+125.0	degrees celsius
Storage Ten	purature Range:
-65.0/+150.0	degrees celsius
Features Pro	vided:
Monolithic an	d bipolar and programmable
Inclosure Ma	terial:
Ceramic	
Inclosure Co	nfiguration:
Dual-in-line	
Output Logi	e Form:
Transistor-tra	nsistor logic
Input Circuit	Pattern:
16 input	
Case Outline	Source And Designator:
D-8 mil-m-38	510
Terminal Su	face Treatment:
Solder	
Voltage Rati	ng And Type Per Characteristic:
12.0 volts in	but
Time Rating	Per Chacteristic:
50.00 nanose	conds propagation delay time, high to low level output and 50.00 nanoseconds
output	
Memory Dev	ісе Туре:
Pal	
Terminal Ty	be And Quantity:
20 printed cir	cuit
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	ion:
Yes - demil/n	li
Fiig:	