NSN 5962-01-351-9510

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-351-9510

Body Length:
0.440 inches
Body Width:
Between 0.245 inches and 0.285 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
55.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 decoder, three to eight line
Case Outline Source And Designator:
F-5 mil-m-38510
Current Rating Per Characteristic:
10.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
24.00 nanoseconds delay
Special Features:
Nuclear hardness critical items
Nuclear Hardness Critical Feature:
Hardened
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

16 flat leads

NSN 5962-01-351-9510

Digital Microcircuit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0