NSN 5962-01-351-9534

Memory Microcircuit - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5962-01-351-9534

Overall Height: 0.400 inches **Body Length:** 1.280 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1.1 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **End Application:** Satellite communications terminal an/usc-3 (v) 1 **Features Provided:** Hermetically sealed and burn in and monolithic and programmed **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 22 input **Case Outline Source And Designator:** D-9 mil-m-38510 **Current Rating Per Characteristic:** 200.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Registered and-or logic array Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 45.00 nanoseconds delay Memory Device Type: Pal **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-351-9534

Memory Microcircuit - Page 2 of 2



Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0