

View Online at <https://aerobasegroup.com/nsn/5962-01-351-9536>

**Overall Length:**

0.540 inches

**Overall Width:**

Between 0.745 inches and 1.040 inches

**Body Length:**

0.540 inches

**Body Width:**

Between 0.245 inches and 0.300 inches

**Body Height:**

Between 0.045 inches and 0.100 inches

**Maximum Power Dissipation Rating:**

303.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

5895-01-299-3419 converter, signal data

**Features Provided:**

Bipolar and programmable and high impedance and w/clock and monolithic

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

14 input

**Case Outline Source And Designator:**

F-9 mil-m-38510

**Current Rating Per Characteristic:**

55.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Product Name:**

4-register and-or-invert gate array

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

50.00 nanoseconds propagation delay time, high to low level output and 50.00 nanoseconds propagation delay time, low to high level output

**Memory Device Type:**

Pal

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0