

View Online at <https://aerobasegroup.com/nsn/5962-01-352-1006>

Overall Height:

0.432 inches

Body Length:

1.490 inches

Body Width:

Between 0.500 inches and 0.610 inches

Body Height:

Between 0.172 inches and 0.217 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

5895-01-299-3419 converter, signal data

Features Provided:

Hermetically sealed and burn in and monolithic and ultraviolet erasable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

25 input

Case Outline Source And Designator:

D-10 mil-m-38510

Current Rating Per Characteristic:

55.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

14.0 volts total supply

Capitance Rating Per Characteristic:

12.00 input picofarads and 14.00 output picofarads

Time Rating Per Characteristic:

120.00 nanoseconds delay

Memory Device Type:

Eprom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0