## NSN 5962-01-352-1043

Memory Microcircuit - Page 1 of 2

Between 0.220 inches and 0.310 inches

Overall Length:
1.280 inches
Overall Height:
0.400 inches
Body Length:
1.280 inches
Body Width:

**Body Height:** 



View Online at https://aerobasegroup.com/nsn/5962-01-352-1043

Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
1.2 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Ultraviolet erasable and monolithic and high impedance and w/clock and asynchronous
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
22 input
Case Outline Source And Designator:
D-9 mil-m-38510
Current Rating Per Characteristic:
100.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
And-or logic array
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
10.00 input picofarads and 10.00 output picofarads
Memory Device Type:
Pal
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## NSN 5962-01-352-1043

Memory Microcircuit - Page 2 of 2



	Ī	erminal	Type	And	Quantit	y:
--	---	---------	------	-----	---------	----

24 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0