NSN 5962-01-352-1876

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-352-1876

Overall Height:

0.400 inches

Body Length:

0.785 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and monolithic and positive outputs and electrostatic sensitive

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 gate, exclusive or

Case Outline Source And Designator:

D-1 mil-m-38510

Current Rating Per Characteristic:

100.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 6.0 volts power source

Capitance Rating Per Characteristic:

10.00 input pascal industrial light tank stock

Time Rating Per Chacteristic:

14.60 nanoseconds delay

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

NSN 5962-01-352-1876

Digital Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

