## NSN 5962-01-352-1877

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-352-1877

| 3  |
|--|
| Overall Height:  |
| 0.400 inches   |
| Body Length:   |
| 1.280 inches   |
| Body Width:  |
| Between 0.220 inches and 0.310 inches  |
| Body Height:   |
| Between 0.140 inches and 0.185 inches  |
| Maximum Power Dissipation Rating:  |
| 500.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and burn in and monolithic and positive outputs  |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Complementary-metal oxide-semiconductor logic  |
| Input Circuit Pattern:   |
| 12 input   |
| Design Function And Quantity:  |
| 1 driver, bus  |
| Case Outline Source And Designator:  |
| D-9 mil-m-38510  |
| Current Rating Per Characteristic:   |
| 5.00 milliamperes supply   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| -0.5 volts power source and 6.0 volts power source   |
| Capitance Rating Per Characteristic:   |
| 10.00 input picofarads and 12.00 output picofarads   |
| Time Rating Per Chacteristic:  |
| 17.00 nanoseconds delay  |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:  |

24 printed circuit

## NSN 5962-01-352-1877

Digital Microcircuit - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0