NSN 5962-01-352-4685

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-352-4685 **Overall Height:** 0.490 inches **Body Length:** Between 1.980 inches and 2.000 inches **Body Width:** Between 0.980 inches and 1.000 inches **Body Height:** 0.230 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and monolithic and hybrid and w/clock and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Design Function And Quantity:** 1 driver **Current Rating Per Characteristic:** 24.20 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Sourcing driver Voltage Rating And Type Per Characteristic: 7.0 volts power source **Hybrid Technology Type:** Monolithic **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 38 pin Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

NSN 5962-01-352-4685

Hybrid Microcircuit - Page 2 of 2



Fiig:

A458a0