## NSN 5962-01-352-7083

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-352-7083

Body Length:
1.280 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
1.2 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
5805-01-187-9399
Features Provided:
Burn in and electrostatic sensitive and bipolar and programmed
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
22 input
Case Outline Source And Designator:
D-9 mil-m-38510
Terminal Surface Treatment:
Solder
Product Name:
Mapping prom
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds access
Memory Device Type:
Pal
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a

## NSN 5962-01-352-7083

Memory Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0