## NSN 5962-01-352-7905

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-352-7905

Overal	ll Leng	th:

Between 1.485 inches and 1.515 inches

**Overall Height:** 

Between 0.430 inches and 0.490 inches

Overall Width:

Between 0.985 inches and 1.015 inches

**Body Length:** 

Between 1.485 inches and 1.515 inches

**Body Width:** 

Between 0.985 inches and 1.015 inches

**Body Height:** 

Between 0.170 inches and 0.200 inches

**Maximum Power Dissipation Rating:** 

225.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**Features Provided:** 

W/switch and w/resistor and monolithic

Inclosure Material:

Ceramic

**Inclosure Configuration:** 

Dual-in-line

**Output Logic Form:** 

Transistor-transistor logic

**Input Circuit Pattern:** 

9 input

**Design Function And Quantity:** 

1 driver, lamp

**Terminal Surface Treatment:** 

Solder

**Product Name:** 

Constant current lamp driver

Voltage Rating And Type Per Characteristic:

31.5 volts power source

**Hybrid Technology Type:** 

Monolithic

**Special Features:** 

Nuclear hardness critical items

**Nuclear Hardness Critical Feature:** 

Hardened

## NSN 5962-01-352-7905

Hybrid Microcircuit - Page 2 of 2



Test	Data	Docum	ent:
------	------	-------	------

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

28 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0