NSN 5962-01-352-7905

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-352-7905

Overal	ll Lengtl	h:

Between 1.485 inches and 1.515 inches

Overall Height:

Between 0.430 inches and 0.490 inches

Overall Width:

Between 0.985 inches and 1.015 inches

Body Length:

Between 1.485 inches and 1.515 inches

Body Width:

Between 0.985 inches and 1.015 inches

Body Height:

Between 0.170 inches and 0.200 inches

Maximum Power Dissipation Rating:

225.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

W/switch and w/resistor and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

9 input

Design Function And Quantity:

1 driver, lamp

Terminal Surface Treatment:

Solder

Product Name:

Constant current lamp driver

Voltage Rating And Type Per Characteristic:

31.5 volts power source

Hybrid Technology Type:

Monolithic

Special Features:

Nuclear hardness critical items

Nuclear Hardness Critical Feature:

Hardened

NSN 5962-01-352-7905

Hybrid Microcircuit - Page 2 of 2



Test	Data	Docum	ent:
------	------	-------	------

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0