## NSN 5962-01-353-3059

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-353-3059

**Overall Length:** 

Between 1.635 inches and 1.680 inches

**Overall Height:** 

Between 0.285 inches and 0.380 inches

**Body Length:** 

Between 1.635 inches and 1.680 inches

**Body Width:** 

Between 0.565 inches and 0.605 inches

**Body Height:** 

Between 0.100 inches and 0.205 inches

**Maximum Power Dissipation Rating:** 

330.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**Features Provided:** 

Burn in and monolithic and w/disable and w/inhibit and bidirectional

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Dual-in-line

**Output Logic Form:** 

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:** 

28 input

**Current Rating Per Characteristic:** 

1.00 milliamperes reverse current, dc blank

**Terminal Surface Treatment:** 

Solder

**Voltage Rating And Type Per Characteristic:** 

-0.6 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:** 

12.00 input picofarads and 15.00 output picofarads

**Time Rating Per Chacteristic:** 

170.00 nanoseconds af output megawatts

**Memory Device Type:** 

**Eprom** 

**Test Data Document:** 

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

32 printed circuit

## NSN 5962-01-353-3059

Memory Microcircuit - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0