NSN 5962-01-354-3852

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-354-3852

Overall Length:
0.840 inches
Overall Height:
0.400 inches
Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
400.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and w/enable and burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
12 input
Design Function And Quantity:
1 multiplexer/demultiplexer, analog
Case Outline Source And Designator:
D-2 mil-m-38510
Current Rating Per Characteristic:
12.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
32.0 volts input/output differential
Capitance Rating Per Characteristic:
10.00 input picofarads and 45.00 output picofarads
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a

NSN 5962-01-354-3852

Linear Microcircuit - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0