## NSN 5962-01-355-3755

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-355-3755						
Body Length:						
2.096 inches						
Body Width:						
Between 0.510 inches and 0.620 inches						
Body Height:						
0.210 inches						
Maximum Power Dissipation Rating:						
1.0 watts						
Operating Tempurature Range:						
-55.0/+125.0 degrees celsius						
Storage Tempurature Range:						
-65.0/+150.0 degrees celsius						
Features Provided:						
Hermetically sealed and burn in and monolithic and positive outputs						
Inclosure Material:						
Ceramic						
Inclosure Configuration:						
Dual-in-line						
Output Logic Form:						
Complementary-metal oxide-semiconductor logic						
Input Circuit Pattern:						
22 input						
Design Function And Quantity:						
1 control						
Case Outline Source And Designator:						
D-5 mil-m-38510						
Current Rating Per Characteristic:						
90.00 milliamperes reverse current, dc absolute						
Terminal Surface Treatment:						
Solder						
Voltage Rating And Type Per Characteristic:						
-0.5 volts power source and 7.0 volts power source						
Capitance Rating Per Characteristic:						
15.00 input picofarads and 25.00 output picofarads						
Time Rating Per Chacteristic:						
33.00 nanoseconds delay						
Test Data Document:						
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).						
Terminal Type And Quantity:						
40 printed circuit						

N/a

Shelf Life:

## NSN 5962-01-355-3755

Digital Microcircuit - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0