NSN 5962-01-355-3759

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-355-3759

Overall Length:
0.785 inches
Overall Height:
0.400 inches
Body Length:
0.785 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
5805-01-188-3993 central office, telephone, automatic
Features Provided:
Monolithic and compatible cmos and hermetically sealed and w/strobe and w/resistor
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 receiver, line differential
Case Outline Source And Designator:
D-1 mil-m-38510
Current Rating Per Characteristic:
30.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 18.0 volts power source
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, high to low level output and 150.00 nanoseconds propagation delay time, low to high level
output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

NSN 5962-01-355-3759

Digital Microcircuit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0