NSN 5962-01-355-3765

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-355-3765

Body Length: 1.280 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and monolithic and low power **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 20 input **Case Outline Source And Designator:** D-9 mil-m-38510 **Current Rating Per Characteristic:** 100.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Capitance Rating Per Characteristic:** 10.00 input picofarads and 12.00 output picofarads **Time Rating Per Chacteristic:** 45.00 nanoseconds access Memory Device Type: Ram **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a

NSN 5962-01-355-3765

Memory Microcircuit - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

