NSN 5962-01-355-7286

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-355-7286

view Offilite at https://defobasegroup.com/nsn/0302-01-000-7200
Overall Length:
Between 0.665 inches and 0.745 inches
Body Length:
Between 0.165 inches and 0.185 inches
Body Outside Diameter:
Between 0.340 inches and 0.370 inches
Overall Diameter:
Between 0.340 inches and 0.370 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-55.0/+150.0 degrees celsius
Features Provided:
Burn in and wideband and monolithic
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, intermediate frequency
Current Rating Per Characteristic:
25.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

NSN 5962-01-355-7286

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0