

View Online at <https://aerobasegroup.com/nsn/5962-01-355-7289>

Overall Length:

0.840 inches

Overall Height:

Between 0.325 inches and 0.400 inches

Body Length:

0.840 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and retriggerable and resettable and w/resistor and w/reset

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Dual 3 input

Design Function And Quantity:

2 multivibrator, monostable

Case Outline Source And Designator:

D-2 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Precision monostable multivibrator

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 18.0 volts power source

Capitance Rating Per Characteristic:

7.50 input picofarads

Time Rating Per Characteristic:

600.00 nanoseconds propagation delay time, high to low level output and 780.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0