

View Online at <https://aerobasegroup.com/nsn/5962-01-356-0178>

Overall Length:

Between 0.342 inches and 0.358 inches

Overall Height:

Between 0.060 inches and 0.100 inches

Overall Width:

Between 0.342 inches and 0.358 inches

Body Length:

Between 0.342 inches and 0.358 inches

Body Width:

Between 0.342 inches and 0.358 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

1.5 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bidirectional and electrostatic sensitive and monolithic and programmable

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

18 input

Case Outline Source And Designator:

C-2 mil-m-38510

Current Rating Per Characteristic:

130.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

And-or array

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Memory Device Type:

Pal

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0