

View Online at <https://aerobasegroup.com/nsn/5962-01-356-0178>

**Overall Length:**

Between 0.342 inches and 0.358 inches

**Overall Height:**

Between 0.060 inches and 0.100 inches

**Overall Width:**

Between 0.342 inches and 0.358 inches

**Body Length:**

Between 0.342 inches and 0.358 inches

**Body Width:**

Between 0.342 inches and 0.358 inches

**Body Height:**

Between 0.060 inches and 0.100 inches

**Maximum Power Dissipation Rating:**

1.5 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Bidirectional and electrostatic sensitive and monolithic and programmable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

18 input

**Case Outline Source And Designator:**

C-2 mil-m-38510

**Current Rating Per Characteristic:**

130.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Product Name:**

And-or array

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Memory Device Type:**

Pal

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0