

View Online at <https://aerobasegroup.com/nsn/5962-01-356-4372>

**Overall Length:**

1.280 inches

**Overall Height:**

Between 0.325 inches and 0.400 inches

**Body Length:**

1.280 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

1.1 watts

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Storage Temperature Range:**

-65.0 to 150.0 degrees celsius

**Features Provided:**

Monolithic and asynchronous and bidirectional and programmable and w/clock and w/enable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

22 input

**Criticality Code Justification:**

Nhcf

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Current Rating Per Characteristic:**

200.00 milliamperes supply

**Terminal Surface Treatment:**

Solder

**Product Name:**

And-or logic array

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Memory Device Type:**

Pal

**Nuclear Hardness Critical Feature:**

Hardened

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0