NSN 5962-01-356-5299

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-356-5299

Body Length:
0.960 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Maximum Power Dissipation Rating:
330.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and high current and high voltage
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
8 input
Design Function And Quantity:
1 array, darlington transistor
Case Outline Source And Designator:
D-6 mil-m-38510
Current Rating Per Characteristic:
20.00 microamperes collector cutoff current, dc, with specified resistance between base and emitter microamperes
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
95.0 volts output
Capitance Rating Per Characteristic:
25.00 input picofarads
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
18 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

NSN 5962-01-356-5299

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0