## NSN 5962-01-356-8600

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-356-8600

Overall Length:0.405 inchesOverall Height:Between 0.325 inches and 0.400 inchesBody Length:10.29 millimetersBody Width:Between 5.59 millimeters and 7.87 millimetersBody Height:3.56 millimetersMaximum Power Dissipation Rating:800.0 milliwattsOperating Tempurature Range:-55.0/+125.0 degrees celsiusStorage Tempurature Range:-55.0/+125.0 degrees celsiusFeatures Provided:Monolithic
Overall Height:         Between 0.325 inches and 0.400 inches         Body Length:         10.29 millimeters         Body Width:         Between 5.59 millimeters and 7.87 millimeters         Body Height:         3.56 millimeters         Maximum Power Dissipation Rating:         800.0 milliwatts         Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Storage Tempurature Range:         -55.0/+125.0 degrees celsius         Features Provided:
Between 0.325 inches and 0.400 inches Body Length: 10.29 millimeters Body Width: Between 5.59 millimeters and 7.87 millimeters Body Height: 3.56 millimeters Maximum Power Dissipation Rating: 800.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Features Provided:
Body Length: 10.29 millimeters Body Width: Between 5.59 millimeters and 7.87 millimeters Body Height: 3.56 millimeters Maximum Power Dissipation Rating: 800.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius
10.29 millimeters Body Width: Between 5.59 millimeters and 7.87 millimeters Body Height: 3.56 millimeters Maximum Power Dissipation Rating: 800.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Features Provided:
Body Width: Between 5.59 millimeters and 7.87 millimeters Body Height: 3.56 millimeters 3.56 millimeters Maximum Power Dissipation Rating: 800.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius
Between 5.59 millimeters and 7.87 millimeters Body Height: 3.56 millimeters Maximum Power Dissipation Rating: 800.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Features Provided:
Body Height:3.56 millimetersMaximum Power Dissipation Rating:800.0 milliwattsOperating Tempurature Range:-55.0/+125.0 degrees celsiusStorage Tempurature Range:-55.0/+125.0 degrees celsiusFeatures Provided:
3.56 millimeters Maximum Power Dissipation Rating: 800.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Features Provided:
Maximum Power Dissipation Rating:800.0 milliwattsOperating Tempurature Range: -55.0/+125.0 degrees celsiusStorage Tempurature Range: -55.0/+125.0 degrees celsius-55.0/+125.0 degrees celsiusFeatures Provided:
800.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Features Provided:
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Features Provided:
-55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Features Provided:
Storage Tempurature Range: -55.0/+125.0 degrees celsius Features Provided:
-55.0/+125.0 degrees celsius Features Provided:
Features Provided:
Monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
2 driver, power
Case Outline Source And Designator:
D-4 mil-m-38510
Current Rating Per Characteristic:
1.50 amperes forward current, peak total value not applicable
Terminal Surface Treatment:
Solder
Product Name:
Dual mosfet driver
Voltage Rating And Type Per Characteristic:
20.0 volts power source
Time Rating Per Chacteristic:
60.00 nanoseconds delay
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
reminar type And walnuty.

## NSN 5962-01-356-8600

Linear Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

