NSN 5962-01-356-8609

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-356-8609

Overall Length:
1.490 inches
Overall Height:
Between 0.357 inches and 0.432 inches
Body Length:
1.490 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
Between 0.172 inches and 0.217 inches
Maximum Power Dissipation Rating:
170.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and ultraviolet erasable and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
15 input
Case Outline Source And Designator:
D-10 mil-m-38510
Current Rating Per Characteristic:
10.00 milliamperes forward current, nonrepetitive, peak total value absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-2.0 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
10.00 input picofarads and 12.00 output picofarads
Time Rating Per Chacteristic:
250.00 nanoseconds access
Memory Device Type:
Eprom
Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-356-8609

Memory Microcircuit - Page 2 of 2



Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0