# NSN 5962-01-357-1200

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-357-1200

## **Body Width:**

Between 0.220 inches and 0.310 inches

## **Body Height:**

Between 0.140 inches and 0.185 inches

## Maximum Power Dissipation Rating:

125.0 milliwatts

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and burn in and monolithic

## **Inclosure Material:**

Ceramic

#### Inclosure Configuration:

Dual-in-line

## **Output Logic Form:**

Emitter-coupled logic

## Input Circuit Pattern:

Triple 2 input

## **Design Function And Quantity:**

3 gate, exclusive, or/nor

## Case Outline Source And Designator:

D-2 mil-m-38510

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-8.0 volts power source and 0.0 volts power source

## Time Rating Per Chacteristic:

1.90 nanoseconds delay

## **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Terminal Type And Quantity:**

16 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

Yes - demil/mli

## Fiig:

A458a0