NSN 5962-01-357-1974

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-357-1974

| Operating Tempurature Range: |
|---|
| -55.0/+125.0 degrees celsius |
| End Application: |
| Milstar |
| Features Provided: |
| Electrostatic sensitive and radiation hardened |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Flat pack |
| Criticality Code Justification: |
| Feat and cbbl and nhcf |
| Design Function And Quantity: |
| 2 driver, switch, field effect transistor |
| Case Outline Source And Designator: |
| -2a mil-m-38510 |
| Product Name: |
| Microcircuit, linear-high speed driver with dual spdt jfet switches |
| Voltage Rating And Type Per Characteristic: |
| -36.0 volts total supply and 36.0 volts total supply |
| Special Features: |
| Radiation hardned iaw esd-82-te-1390b; esd; hci |
| Nuclear Hardness Critical Feature: |
| Hardened |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |