## NSN 5962-01-358-5651

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-358-5651

Body Length:
Between 0.442 inches and 0.460 inches
Body Height:
Between 0.060 inches and 0.100 inches
Maximum Power Dissipation Rating:
0.473 milliwatts
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Storage Tempurature Range:
-65.0 to 150.0 degrees celsius
Features Provided:
Monolithic and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 converter, analog to digital
Case Outline Source And Designator:
C-4 mil-m-38510
Current Rating Per Characteristic:
200.00 milliamperes supply
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.6 volts power source
Capitance Rating Per Characteristic:
22.00 input picofarads
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:
28 leadless
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

## NSN 5962-01-358-5651

Digital-linear Microcircuit - Page 2 of 2



Fiig:

A458a0