

View Online at <https://aerobasegroup.com/nsn/5962-01-358-8680>

Body Length:

1.400 inches

Body Width:

0.594 inches

Body Height:

0.280 inches

Maximum Power Dissipation Rating:

4.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and monolithic and positive outputs

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

9 input

Current Rating Per Characteristic:

50.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

35.00 input picofarads and 40.00 output picofarads

Time Rating Per Characteristic:

85.00 nanoseconds delay

Memory Device Type:

First-in first-out

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0