NSN 5962-01-358-9064

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-358-9064 **Body Length:** 0.405 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and high speed and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 comparator **Case Outline Source And Designator:** D-4 mil-m-38510 **Current Rating Per Characteristic:** 18.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Latching comparator **Voltage Rating And Type Per Characteristic:** 16.5 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-358-9064

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0