NSN 5962-01-359-2044

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-359-2044

view Offilite at https://defobasegroup.com/nsi//0302-01-003-2044
Body Length:
Between 0.442 inches and 0.460 inches
Body Width:
Between 0.442 inches and 0.460 inches
Body Height:
Between 0.060 inches and 0.100 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and programmable and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
20 input
Case Outline Source And Designator:
C-4 mil-m-38510
Current Rating Per Characteristic:
250.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Memory Device Type:
Prom
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
28 leadless
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0