

View Online at <https://aerobasegroup.com/nsn/5962-01-359-7665>

Body Length:

1.111 inches

Body Width:

Between 0.350 inches and 0.410 inches

Body Height:

0.210 inches

Maximum Power Dissipation Rating:

495.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

6625-01-260-2936

Features Provided:

Hermetically sealed and burn in and monolithic and static operation

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

16 input

Case Outline Source And Designator:

D-7 mil-m-38510

Current Rating Per Characteristic:

90.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

6.00 input picofarads and 7.00 output picofarads

Time Rating Per Characteristic:

35.00 nanoseconds delay

Memory Device Type:

Ram

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

22 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0