## NSN 5962-01-360-1552

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-360-1552

Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
303.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Burn in and bipolar and monolithic and programmed
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Bipolar metal-oxide semiconductor
Input Circuit Pattern:
16 input
Case Outline Source And Designator:
D-8 mil-m-38510
Current Rating Per Characteristic:
1.00 milliamperes input
Terminal Surface Treatment:
Solder
Product Name:
Microcircuits, digital, bipolar, programmable logic, monolithic silicon
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Memory Device Type:
Pal
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 5962-01-360-1552

Memory Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

