

View Online at <https://aerobasegroup.com/nsn/5962-01-360-4022>

Body Length:

0.960 inches

Body Width:

0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

950.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bipolar and burn in and high impedance and monolithic and programmed and schottky and tested to mil-std-883 and thin film and w/active pull-up and 3-state output

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Emitter-coupled logic

Input Circuit Pattern:

13 input

Case Outline Source And Designator:

D-6 mil-m-38510

Current Rating Per Characteristic:

170.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Prom with active pullup and a third high-impedance state output

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

125.00 nanoseconds propagation delay

Memory Device Type:

Prom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

18 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0